



Tool Comparison Chart



Electric Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
K7-1*	5" Wide	115V	¼	9	50-75
K7-2*	5" Wide	230V	¼	9	50-75
K7-1E*	8" Wide	115V	¼	11	65-90
K7-2E*	8" Wide	230V	¼	11	65-90
M5-1*	8" Wide	115V	½	21	70-100
M5-2*	8" Wide	230V	½	21	70-100
M5-1E*	12" Wide	115V	½	27	100-150
M5-2E*	12" Wide	230V	½	27	100-150
W1E	5" Wide	115V	2	97	250-350

*Denotes dust containment attachment available

Pneumatic Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
KP5*	5" Wide	42CFM/	70-100 PSI	¾	6 50-75
KP5E	8" Wide	42CFM/	70-100 PSI	¾	8 65-90
MP6*	8" Wide	42CFM/	70-100 PSI	2.5	17 70-100
MP6E*	12" Wide	42CFM/	70-100 PSI	2.5	23 100-150

*Denotes dust containment attachment available

Gas Models

Model	Clearing Area	Power Supply	Horsepower	Weight (lbs)	Removal Rate (Sq. ft. per hour)
W1G*	5" Wide	Gas	5	92	250-350

Serving the world with quality surface preparation tools since 1937!